



REMARKS
1. All dimensions to panel edge include EVA overlap unless otherwise specified.
2. "####" etching refers to Voltaic's PO# for traceability
3. Note the red circled inspection items

Voltaic

Drawing Details		Construction		Power Specifications				
Panel Number	P122	All Materials RoHS Compliant		Output Tolerance: ± 10% of Voltage and Current				
Revision	R2A	Substrate	DOUBLE SIDED PCB	Solar Cell: SUNPOWER MAXEON GEN III				
Engineer	AK	Encapsulant	EVA F806P	Nominal Efficiency: ≥24.4%		Cell Pieces 10S1P		10
Approval	SM 2025-08-26	Top Layer	R045E ETFE	Panel Electrical Rating		Nominal	Expected	
Date Created	2022-01-26	Top Layer Pattern	YH05	Open-Circuit Voltage	Voc	7.28	7.07	V
Date Modified	2025-08-26	Wire Number	N/A	Voltage at Max Power	Vp	6.23	6.01	V
Changes	CELL PIECE SIZE, SILKSCREEN	Measured Wire Length	N/A	Short-Circuit Current	Isc	0.069	0.064	A
Tolerance: ±0.3 mm	Units: mm	Strain Relief	NONE	Current at Max Power	Ip	0.065	0.057	A
Scale: 1.25:1	Sheet: 1/2	Attachment	NONE	Maximum Power	Wp	0.405	0.341	W

This document contains proprietary information and may not be copied or shared without the consent of Voltaic Systems



Voltaic

Cell Cut Diagram	
Cell	SUNPOWER MAXEON GEN III
Cell Efficiency	≥24.4%
Panel Reference	P122
Panel Revision	R2A
Date Created	2022-01-26
Date Modified	2025-08-26
Approval	SM 2025-08-26
Tolerance: ±0.3 mm	Units: mm
Scale: 1:1	Sheet: 2/2

This document contains proprietary information and may not be copied or shared without the consent of Voltaic Systems