


REMARKS
1. "####" refers to Voltaic's PO# for traceability
2. Please note red circled inspection items
3. **Please note the corner piece placement**

Voltaic

Drawing Details		Construction		Power Specifications			
Panel Number	P151	All Materials RoHS Compliant		Output Tolerance: ± 10% of Voltage and Current			
Revision	R6A	Substrate	BLACK KPF	Solar Cell: EUROPEAN MONOCRYSTALLINE M182 10BB			
Engineer	AK	Encapsulant	EVA F806P	Nominal Efficiency: ≥23.2%	Cell Pieces:	30	
Approval	SM 2025-06-26	Top Layer	TEMPERED GLASS	Panel Electrical Rating			
Date Created	2021-02-03	Top Layer Pattern	N/A	Open-Circuit Voltage	Voc	19.6	V
Date Modified	2025-06-26	Wire Number	W249	Voltage at Max Power	Vp	16.9	V
Changes	NEW EUROPEAN CELLS	Measured Wire Length	1000	Short-Circuit Current	Isc	6.5	A
Tolerance: ±0.3 mm	Units: mm	Strain Relief	J-BOX	Current at Max Power	Ip	5.9	A
Scale: 1:13	Sheet: 1/4	Attachment	BLACK ALUMINIUM FRAME	Maximum Power	Wp	100	W

This document contains proprietary information and may not be copied or shared without the consent of Voltaic Systems


Voltaic

Model Number	P151 R6A
Number of cell pieces	30
Open Circuit Voltage (Voc)	19.6 V
Max Power Point Voltage (Vp)	16.9 V
Short Circuit Current (Isc)	6.5 A
Max Power Point Current (Ip)	5.9 A
Max Power (Wp)	100 W

Voltaic

Drawing Details		Construction		Power Specifications			
Panel Number	P151	All Materials RoHS Compliant		Output Tolerance: ± 10% of Voltage and Current			
Revision	R6A	Substrate	BLACK KPF	Solar Cell: EUROPEAN MONOCRYSTALLINE M182 10BB			
Engineer	AK	Encapsulant	EVA F806P	Nominal Efficiency: ≥23.2%		Cell Pieces:	30
Approval	SM 2025-06-26	Top Layer	TEMPERED GLASS	Panel Electrical Rating			
Date Created	2021-02-03	Top Layer Pattern	N/A	Open-Circuit Voltage	Voc	19.6	V
Date Modified	2025-06-26	Wire Number	W249	Voltage at Max Power	Vp	16.9	V
Changes	NEW EUROPEAN CELLS	Measured Wire Length	1000	Short-Circuit Current	Isc	6.5	A
Tolerance: ±0.3 mm	Units: mm	Strain Relief	J-BOX	Current at Max Power	Ip	5.9	A
Scale: 1:1	Sheet: 2/4	Attachment	ALUMINIUM FRAME	Maximum Power	Wp	100	W


This document contains proprietary information and may not be copied or shared without the consent of Voltaic Systems




Voltaic

Cell Cut Diagram	
Cell	EUROPEAN MONOCRYSTALLINE M182 10BB
Cell Efficiency	>23.2%
Panel Reference	P151
Panel Revision	R6A
Date Created	2021-02-03
Date Modified	2025-06-26
Approval	SM 2025-06-26
Tolerance: ±0.3 mm	Units: mm
Scale: 1:1.7	Sheet: 3/4

This document contains proprietary information and may not be copied or shared without the consent of Voltaic Systems




Panel with Protective Corner Pieces



Protective Corner Piece:
EPE Foam/Cardboard base

Thickness: 6mm
T Liner
125GSM
BC Flute (Double walled)
Print in Black



Voltaic

Drawing Details		Construction		Power Specifications			
Panel Number	P151	All Materials RoHS Compliant		Output Tolerance: ± 10% of Voltage and Current			
Revision	R6A	Substrate	BLACK KPF	Solar Cell		EUROPEAN MONOCRYSTALLINE M182 10BB	
Engineer	AK	Encapsulant	EVA F806P	Nominal Efficiency: ≤23.2		Cell Pieces:	30
Checked By	SM 2025-06-26	Top Layer	TEMPERED GLASS	Panel Electrical Rating			
Date Created	2021-02-03	Wire Number	W249	Open-Circuit Voltage	Voc	19.6	V
Date Modified	2025-06-26	Wire Length	1000	Voltage at Max Power	Vp	16.9	V
Changes	NEW EUROPEAN CELLS	Strain Relief	J-BOX	Short-Circuit Current	Isc	6.5	A
Tolerance: ±0.3 mm	Units: mm	Attachment	ALUMINIUM FRAME	Current at Max Power	Ip	5.9	A
Scale: 1:25	Sheet: 4/4			Maximum Power	Wp	100	W

This document contains proprietary information and may not be copied or shared without the consent of Voltaic Systems